

Excel Fast Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 2/6/2018

Version: 1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Excel Fast Part A

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For Rx Only

1.3. Supplier

Manufacturer

Reliance Orthodontic Products, Inc. 1540 West Thorndale Ave.
Itasca, IL 60143 USA
630-773-4009, during normal business hours
www.relianceorthodontics.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - 24-Hour Hazmat Emergency Communications Center
Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2B	H320	Causes eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H320 - Causes eye irritation

Precautionary statements (GHS-US) :

P261 - Avoid breathing vapors
P264 - Wash hands thoroughly after handling
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear eye protection, face protection, protective gloves
P302+P352 - If on skin: Wash with plenty of Wash skin with soap and water
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P321 - Specific treatment (see First aid measures on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P363 - Wash contaminated clothing before reuse
P501 - Dispose in a safe manner in accordance with local/national regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Excel Fast Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Fused Silica	(CAS-No.) 60675-86-0	10 - 30	Skin Irrit. 2, H315
BisGMA	(CAS-No.) 1565-94-2	10 - 30	Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Skin Sens. 1, H317
Hydrogen Chloride, liquefied, under pressure	(CAS-No.) 7647-01-0	1 - 5	Press. Gas (Liq.), H280 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1A, H314
Dibenzoyl Peroxide, technically pure	(CAS-No.) 94-36-0	< 1	Org. Perox. B, H241 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Mild eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing mist, vapors.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

Excel Fast Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing mist, vapors.
- Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Fused Silica (60675-86-0)		
Not applicable		
Hydrogen Chloride, liquefied, under pressure (7647-01-0)		
Not applicable		
BisGMA (1565-94-2)		
Not applicable		
Dibenzoyl Peroxide, technically pure (94-36-0)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (Benzoyl peroxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Protective goggles

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Solid
- Appearance : Paste.
- Color : White / Light Beige
- Odor : Acrylic
- Odor threshold : No data available
- pH : No data available
- Melting point : No data available
- Freezing point : Not applicable
- Boiling point : No data available
- Flash point : Not applicable
- Relative evaporation rate (butyl acetate=1) : No data available

Excel Fast Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: Not applicable
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Fused Silica (60675-86-0)	
LD50 oral rat	N/A
LD50 dermal rat	N/A
LD50 dermal rabbit	N/A
LC50 inhalation rat (ppm)	N/A

Hydrogen Chloride, liquefied, under pressure (7647-01-0)	
LC50 inhalation rat (mg/l)	8.3 mg/l air (30 minutes, Rat, Male, Experimental value)
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

Dibenzoyl Peroxide, technically pure (94-36-0)	
LD50 oral rat	> 5000 mg/kg (Rat)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Excel Fast Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Fused Silica (60675-86-0)	
IARC group	4 - Probably not carcinogenic to humans

Dibenzoyl Peroxide, technically pure (94-36-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Fused Silica (60675-86-0)	
LOAEL (oral, rat)	N/A mg/kg body weight
LOAEL (dermal, rat/rabbit)	N/A mg/kg body weight
LOAEC (inhalation, rat, gas)	N/A ppmV/4h
LOAEC (inhalation, rat, vapour)	N/A mg/l/4h
LOAEC (inhalation, rat, dust/mist/fume)	N/A mg/l/4h

Specific target organ toxicity – repeated exposure : Not classified

Fused Silica (60675-86-0)	
LOAEL (oral, rat, 90 days)	N/A mg/kg bodyweight/day
LOAEL (dermal, rat/rabbit, 90 days)	N/A mg/kg bodyweight/day
LOAEC (inhalation, rat, gas, 90 days)	N/A ppmV/6h/day
LOAEC (inhalation, rat, vapour, 90 days)	N/A mg/l/6h/day
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	N/A mg/l/6h/day

Aspiration hazard : Not classified

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Mild eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Hydrogen Chloride, liquefied, under pressure (7647-01-0)	
LC50 fish 1	282 mg/l (96 h, Gambusia affinis, Fresh water, Literature study)
EC50 Daphnia 1	< 56 mg/l (72 h, Daphnia magna, Literature study)
LC50 fish 2	pH 3.25-3.5 (Other, 96 h, Lepomis macrochirus, Semi-static system, Fresh water, Experimental value)
EC50 Daphnia 2	pH 4.92 (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

Dibenzoyl Peroxide, technically pure (94-36-0)	
LC50 fish 1	2 mg/l (LC50; 96 h; Poecilia reticulata)

12.2. Persistence and degradability

Hydrogen Chloride, liquefied, under pressure (7647-01-0)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

Dibenzoyl Peroxide, technically pure (94-36-0)	
Persistence and degradability	Readily biodegradable in water. No (test) data on mobility of the substance available.

12.3. Bioaccumulative potential

Hydrogen Chloride, liquefied, under pressure (7647-01-0)	
Log Pow	0.25 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Excel Fast Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dibenzoyl Peroxide, technically pure (94-36-0)

Log Pow	3.71 (QSAR; 3.2; Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 22 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Hydrogen Chloride, liquefied, under pressure (7647-01-0)

Ecology - soil	Not applicable (gas). May be harmful to plant growth, blooming and fruit formation.
----------------	---

12.5. Other adverse effects

Effect on the global warming	: No known effects from this product.
GWPMix comment	: No known effects from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

TDG

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Dibenzoyl Peroxide, technically pure (94-36-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

Dibenzoyl Peroxide, technically pure (94-36-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Excel Fast Part A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H241	Heating may cause a fire or explosion
H280	Contains gas under pressure; may explode if heated
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H331	Toxic if inhaled
H401	Toxic to aquatic life

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.